

TANKER CALIBRATION CHART

TANK CALIBRATED BY COAST INSTRUMENT & TANK ENGINEERS.

(On Norma Baya KCM 170 B)

VEHICLE OWNED BY: Razon Transporters Ltd.
MAKE AND REGISTRATION No. Semi Trailer GP 7654

P.O. BOX 86086-80100
PHONE: 0725 944469
MOMBASA

163.55 COMPARTMENT (1)		188.05 COMPARTMENT (2)		187.7 COMPARTMENT (3)	
DIP CM	CAPACITY CU. METER	Dip CM	Capacity Cu. Meter	DIP CM	CAPACITY CU. METER
12.5	1.00	18.55	1.00	23.2	1.00
24.7	2.00	30.8	2.00		
35.7	3.00	42.6	3.00	47.7	2.00
45.25	4.00	51.5	4.00	64.75	3.00
55.35	5.00	61.4	5.00		
64.6	6.00	70.6	6.00	80.35	4.00
74.55	7.00	79.8	7.00	96.0	5.00
		88.3	8.00		
83.35	8.00	97.3	9.00	112.05	6.00
		106.7	10.00		
92.55	9.00	115.05	11.00	127.8	7.00
101.7	10.00	124.0	12.00		
111.5	11.00	133.35	13.00	145.2	8.00
121.2	12.00	143.15	14.00		
131.6	13.00	153.6	15.00	165.0	9.00
142.85	14.00	164.8	16.00		
156.0	15.00	178.4	17.00	178.0	9.50

CALIBRATION CHARTS WITH APPROPRIATE DIP STICKS ARE THE GUIDANCE FOR LOADING AND OFF-LOADING PRODUCTS AT BONDED OIL INSTALLATIONS. METER WHICH IS CALIBRATED AND SEALED BY THE WEIGHTS & MEASURES DEPARTMENT BE USED TO VERIFY.

H.B. Line "E." MUST be Level with tube top when taking dip.

Volume based at 20°C.

24/11/2018 (U.M) 8188

